

# Material Safety Data Sheet: FREE AEROSOL

Supersedes Date 01/13/2011

Issuing Date 10/17/2013

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name FREE AEROSOL  
Recommended use Lubricant  
Information on Manufacturer  
CERTIFIED LABS, DIV. OF NCH CORP.  
BOX 152170  
IRVING, TEXAS 75015

Product Code 5C68  
Chemical nature Solvent blend  
Emergency Telephone Number  
CHEMTREC® 800-424-9300

## 2. HAZARDS IDENTIFICATION

Emergency Overview  
DANGER  
Extremely flammable  
May be harmful if inhaled  
Causes skin irritation  
Causes eye irritation  
May be harmful if swallowed

Color Amber

Physical State Liquid

Odor Petroleum distillates

Potential Health Effects

Principle Route of Exposure

Primary Routes of Entry

Acute Effects

Eyes

Skin

Inhalation

Ingestion

Chronic Toxicity

Target Organ Effects

Aggravated Medical Conditions

Potential Environmental Effects

Inhalation, Skin contact, Eye contact.  
Inhalation, Skin Absorption.

Causes eye irritation.

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways. Repeated and prolonged exposure to solvents may cause brain and nervous system damage. Liver and kidney injuries may occur.

Central nervous system, Cardiovascular system, Respiratory system, Liver, Kidney.

Respiratory system, Skin disorders, Neurological disorders, Liver disorders, Kidney disorders.

See Section 12 for additional Ecological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No
Petroleum distillates, hydrotreated light	64742-47-8
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5
Solvent naphtha (petroleum), medium aliphatic	64742-88-7
Ethyl acetate	141-78-6
Sodium sulfonate	68608-26-4
Propane	74-98-6
Butane	106-97-8

## 4. FIRST AID MEASURES

General advice

Eye Contact

Skin Contact

Inhalation

Ingestion

Notes to physician

Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.

Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

## 5. FIRE-FIGHTING MEASURES

Flash Point	> 80 °F / > 27 °C	Method	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air % Solvent mixture.		Upper 11.5	Lower 0.5
Suitable Extinguishing Media	Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical	Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >24 inches / >61 cm and Bumback: >3 inch / >7.5 cm. Material can create slippery conditions.		
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure -demand, MSHA/NIOSH (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) -	3		
NFPA	Health 2	Flammability 4	Instability 0
HMS	Health 2	Flammability 4	Instability 0

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non -combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13)
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

## 7. HANDLING AND STORAGE

Handling	Keep away from heat and sources of ignition. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing.			
Storage	Keep away from open flames, hot surfaces and sources of ignition. Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	Heated Refrigerated

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light	5 mg/m <sup>3</sup> as oil mist	10 mg/m <sup>3</sup> as oil mist	No data available
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	TWA: 5 mg/m <sup>3</sup> , STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	IDLH: 2,500 mg/m <sup>3</sup> ; STEL 10 mg/m <sup>3</sup> ; TWA: 5 mg/m <sup>3</sup>
Solvent naphtha (petroleum), medium aliphatic	No data available	No data available	No data available
Ethyl acetate	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
Sodium sulfonate	No data available	No data available	No data available
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side -shields.
Skin Protection	Wear suitable protective clothing. Impervious gloves.
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
General Hygiene Considerations	Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re -use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Non viscous
Color	Amber	Odor	Petroleum distillates
Appearance	Transparent - Hazy	pH	Not applicable
Specific Gravity	0.840	Evaporation Rate	24.77 (Butyl acetate=1)
Percent Volatile (Volume)	75.4	VOC Content (%)	41.901
VOC Content (g/L)	352	Vapor Pressure	1547 mmHg @ 70 °F
Vapor Density	1.7	Solubility	Negligible
Boiling Point/Range	> 160 °F / 71 °C		

## 10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition
Incompatible Products	Strong oxidizing agents, Reducing agents, Strong acids, Strong bases, Amines, Nitric acid.
Hazardous Decomposition Products	Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides, Aldehydes, Ketones, Hydrocarbons.
Possibility of Hazardous Reactions	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

**Product Information** No information available.

### Component Information

#### Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Petroleum distillates, hydrotreated light	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h	no data available	no data available
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	no data available	no data available	no data available
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h	no data available	no data available
Ethyl acetate	= 5620 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	no data available	no data available	no data available
Sodium sulfonate	no data available	no data available	no data available	no data available	no data available
Propane	no data available	no data available	= 658 mg/L ( Rat ) 4 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m <sup>3</sup> ( Rat ) 4 h	no data available	no data available

#### Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Petroleum distillates, hydrotreated light	no data available	no data available	no data available	no data available	respiratory system, liver, kidney, CNS
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	no data available	no data available	no data available	no data available	respiratory system
Solvent naphtha (petroleum), medium aliphatic	no data available	no data available	no data available	no data available	CNS, liver, kidneys
Ethyl acetate	no data available	no data available	no data available	no data available	eyes, respiratory system, skin
Sodium sulfonate	no data available	no data available	no data available	no data available	no data available
Propane	no data available	no data available	no data available	no data available	CNS, heart
Butane	no data available	no data available	no data available	no data available	CNS, heart

#### Carcinogenicity

There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
Petroleum distillates, hydrotreated light	not applicable	not applicable	not applicable	not applicable	not applicable
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	not applicable	not applicable	not applicable	not applicable	not applicable
Solvent naphtha (petroleum), medium aliphatic	not applicable	not applicable	not applicable	not applicable	not applicable
Ethyl acetate	not applicable	not applicable	not applicable	not applicable	not applicable
Sodium sulfonate	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable
Butane	not applicable	not applicable	not applicable	not applicable	not applicable

## 12. ECOLOGICAL INFORMATION

### Product Information

No information available.

### Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Petroleum distillates, hydrotreated light	no data available	LC50 = 45 mg/L Pimephales promelas 96 h LC50 = 2.2 mg/L Lepomis macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h	no data available	LC50= 4720 mg/L 96 h	N/A
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	no data available	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	no data available	EC50> 1000 mg/L 48 h	N/A
Solvent naphtha (petroleum), medium aliphatic	EC50 = 450 mg/L Pseudokirchneriella subcapitata 96 h	LC50 = 800 mg/L Pimephales promelas 96 h	no data available	EC50> 100 mg/L 48 h	N/A
Ethyl acetate	EC50 = 3300 mg/L Desmodesmus subspicatus 48 h	LC50 220 - 250 mg/L Pimephales promelas 96 h LC50 = 484 mg/L Oncorhynchus mykiss 96 h LC50 352 - 500 mg/L Oncorhynchus mykiss 96 h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50= 560 mg/L 48 h	0.6
Sodium sulfonate	no data available	no data available	no data available	no data available	N/A
Propane	no data available	no data available	no data available	no data available	2.3
Butane	no data available	no data available	no data available	no data available	2.89

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available.

### Mobility

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Product Disposal

Dispose of in accordance with local regulations.

### Container Disposal

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

## 14. TRANSPORT INFORMATION

### DOT

Proper Shipping Name	Consumer Commodity
Hazard Class	ORM-D
Description	Consumer Commodity, ORM-D

### TDG

Proper shipping name	Consumer Commodity
Hazard Class	ORM-D
UN-No	UN1950
Description	Consumer Commodity, ORM-D

### ICAO

UN-No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
Shipping Description	UN1950, Aerosols, flammable, 2.1, LTD QTY

### IATA

UN-No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
ERG Code	126
Shipping Description	UN1950, Aerosols, flammable, 2.1, LTD QTY

### IMDG/IMO

Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
UN-No	UN1950
EmS No.	F-A, S-A
Shipping Description	UN1950, Aerosols, flammable, 2.1, LTD QTY

## 15. REGULATORY INFORMATION

### Inventories

TSCA

Complies

DSL

Complies

### U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

#### CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Petroleum distillates, hydrotreated light	Not applicable	Not applicable
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	Not applicable	Not applicable
Solvent naphtha (petroleum), medium aliphatic	Not applicable	Not applicable
Ethyl acetate	5000 lb	Not applicable
Sodium sulfonate	Not applicable	Not applicable
Propane	Not applicable	Not applicable
Butane	Not applicable	Not applicable

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS Hazard Class

A Compressed gases B2 Flammable liquid D2B Toxic materials



## 16. OTHER INFORMATION

Prepared By

Devon Kebodeaux

Supersedes Date

01/13/2011

Issuing Date

10/17/2013

Reason for Revision

No information available.

Glossary

No information available.

List of References.

No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.