# Material Safety Data Sheet

#### Kool Rite 2290 Metal Working Fluid

Date of Preparation: April 2005; Updated May 2008

HMIS

1

0

**H** 1

F

R

PPE<sup>†</sup>

<sup>†</sup>Sec. 8

#### Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** Metal Working Fluid – Kool Rite 2290 **Chemical Formula:** 2006-6R1

**Manufacturer:** JTM Products, Inc., 31025 Carter Street, Solon, OH 44139, Phone (440) 287-2302, FAX (440) 287-3095 (CHEM-TEL 24-hour emergency: (800) 255-3924)

#### Section 2 - Composition / Information on Ingredients (CAS#)

Non-hazardous proprietary blend containing:

Hydrotreated naphthenic oil (TLV =  $5 \text{ mg/m}^3$ , mist) CAS #64742-52-5 less than 35% by weight

## Section 3 - Hazards Identification

#### ☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

#### **Potential Health Effects**

**Eyes:** This product is an eye irritant. Avoid eye contact.

**Skin:** This product is an eye initiant. Avoid eye contact. **Skin:** This product may cause skin irritation. Avoid prolonged skin contact. Product is slightly irritating.

Prolonged or repeated exposure may result in disorders such as dermatitis.

**Inhalation:** This product may irritate the lungs if inhaled as a mist. Avoid breathing mists and sprays. Breathing high vapor concentrations may cause dizziness, nausea, headache and loss of coordination.

**Ingestion:** This product is slightly toxic if ingested. Avoid ingestion.

Carcinogenicity: IARC, NTP, and OSHA do not list these ingredients as carcinogens.

#### Section 4 - First Aid Measures

**Eye Contact:** Flush with copious volumes of water for 15 minutes while holding eyelids open. Seek medical attention. **Skin Contact:** Wash with water or soap/water. Clean clothing before reuse. If irritation is present, seek medical attention. **Inhalation:** For mist exposure, remove to fresh air. Use artificial breathing and oxygen as needed. Seek medical attention. **Ingestion**: Do not induce vomiting. If large quantities are ingested, seek medical attention.

#### **Section 5 - Fire-Fighting Measures**

Flash Point: 335 °F	LEL: NA	NFPA
Flash Point Method: TCC	UEL: NA	$\langle 1 \rangle$
Autoignition Temperature: NA	Flammability Classification: 1	
<b>Extinguishing Media:</b> Water, water fog, alcohol foam, carbon dioxide or dry chemical are all suitable. $1 \times 0$		
Fire or Explosion Hazards: Can be made to burn.		
Hazardous Combustion Products: Carbon dioxide, carbon monoxide, partially burned hydrocarbons.		
Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.		
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing		
apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.		

#### Section 6 - Accidental Release Measures

**Spill /Leak Procedures:** This product is made of NON-biodegradable oils and additives.

**Containment:** For large spills, dike far ahead of liquid spill for later disposal. Shut off ignition sources.

Cleanup: Place the bulk of any spilled material into drums, then absorb any remaining material on inert material. Wash

with suitable cleaners. Discard in accordance with any applicable regulations.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

#### Section 7 - Handling and Storage

Handling Precautions: Handle as a combustible petroleum oil. Storage Requirements: Store away from heat in closed containers

### Kool Rite 2290 Metal Working Fluid

#### **Section 8 - Exposure Controls / Personal Protection**

Ventilation: Provide general or local exhaust ventilation systems.

**Respiratory Protection:** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses. Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

#### Section 9 - Physical and Chemical Properties

Physical State: Liquid Appearance and Odor: amber liquid, oil odor Vapor Pressure: NA Vapor Density (Air=1): NA Formula Weight: NA (blend) Density: ~8.22 lbs./gal. pH: 9.5 Water Solubility: emulsion/soluble Boiling Point: mixture, contains water Freezing/Melting Point: N/A Evaporation Rate: N/A Specific Gravity (H<sub>2</sub>O=1, at 4 °C): 1.0

#### Section 10 - Stability and Reactivity

Stability: Kool-Rite 2290 is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization will not occur.

Chemical Incompatibilities: none

Conditions to Avoid: Avoid contact with strong oxidizing agents and ignition sources.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce oxides of carbon.

## Section 11- Toxicological Information

Eye Effects: Eye irritant.

**Skin Effects:** Slight skin irritant if allowed to remain in contact.

## **CONTAINS NO CARCINOGENS !**

#### **Section 12 - Ecological Information**

Environmental Fate

Environmental Transport: Unknown.

Environmental Degradation: Unknown. Ingredients used are not expected to be biodegradable.

Soil Absorption/Mobility: Unknown.

## Section 13 - Disposal Considerations

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

#### Section 14 - Transport Information

**DOT labeling:** Petroleum Lubricant [Flash point above 300°F] National Motor Freight Class = 65

#### **Section 15 - Regulatory Information**

**EPA Regulations:** All ingredients are on the TSCA inventory. SARA title III section 313 component reporting hydrotreated naphthenic oil ( $TLV = 5 \text{ mg/m}^3$ , mist) CAS #64742-52-5, less than 35% by weight . Not a RCRA hazardous waste.

## Section 16 - Other Information

Prepared By: D. Barrer

#### Approved By: J. Cahoon

**Disclaimer:** JTM PRODUCTS, INC. makes no warranty, expressed or implied, as to the accuracy, completeness, or reliability of information contained herein, except that such information is, to the best of JTM's knowledge and belief, accurate as of the date indicated. It is for the purchaser and/or user to decide whether this information is suitable for his purposes. May ,2008 Updated Section 2