

MATERIAL SAFETY DATA SHEET



PRODUCT CODE: #1772 TEXTURED CEILING PAINT, #2052 SMOOTH TEXTURED WALL PAINT AND #2062 SAND TEXTURED WALL PAINT
 HMIS CODES: H F R P
 1 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Litex Inc.

ADDRESS: 5985 NW 31ST Avenue, Fort Lauderdale, FL 33309

EMERGENCY PHONE: (954) 970-0361

DATE PREPARED: 10/25/01

INFORMATION PHONE: (800) 340-0361

NAME OF PREPARER: Gene O'Neill

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
	CAS NUMBER	OSHA PEL	ACGIH TLV		
Hydrous Magnesium Aluminum Silicate/Minugel FG	8031-18-3	5 mg/m ³	10 mg/m ³	N/A	1.79
Calcium Carbonate	471-34-1		10 mg/m	N/A	30
Silicon Dioxide	4808-60-7	15mg/m ³	15 mg/m ³	N/A	<20

Silicon Dioxide applies to #2062 Sand Textured Wall Paint Only.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A

VAPOR DENSITY: N/A

COATING V.O.C.: 0.0 LB/GL (0 GR/LT)

APPEARANCE AND ODOR: White textured appearance with a mild odor.

SPECIFIC GRAVITY: 1.5

EVAPORATION RATE: Slower than ether

SOLUBILITY IN WATER: Product is dilutable with water

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: N/A • UPPER: N/A

EXTINGUISHING MEDIA: Foam, Dry Chemical, Water Fog

SPECIAL FIREFIGHTING PROCEDURES: Self-contained breathing apparatus and turn-out gear. This product does not support combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known. Product can splatter above 212 F.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Avoid open flame, welding arcs and other high temperature sources that may produce thermal decomposition.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts could coagulate the product.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None known.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: When spraying or sanding, prolonged inhalation may result in respiratory disease, including silicosis, pneumoconiosis and pulmonary fibrosis. Smoking can increase this risk of injury. The health effects of continuous breathing fine crystalline silica dust (sand) can be carcinogenic to humans. Individuals with pulmonary and/or respiratory disease, including but not limited to, asthma and bronchitis, or subject to eye irritation, should be precluded from exposure. *This paragraph applies to #2062 SAND TEXTURED WALL PAINT only.*

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Slight amine odor. May cause slight discomfort or irritation of the nasal passages. *This paragraph applies to #1772 TEXTURED CEILING PAINT AND #2052 SMOOTH TEXTURED WALL PAINT only.*

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause some eye irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: No data established.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Swallowing of the product may cause some gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC): Repeated and prolonged overexposure may produce nasal and respiratory irritation.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No *No known carcinogen contained in this product. This paragraph applies to #1772 TEXTURED CEILING PAINT AND #2052 SMOOTH TEXTURED WALL PAINT only.*

CARCINOGENICITY: IARC MONOGRAPHS? Yes Level I Grouping Symptoms of excessive exposure include shortness of breath and reduced pulmonary function. The inert material gives no potential acute toxic hazard. *This paragraph applies to #2062 SAND TEXTURED WALL PAINT only.*

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: No data established.

EMERGENCY AND FIRST AID PROCEDURES: For eye contact, flush with running water. Seek medical advice if necessary. For skin contact, flush with lukewarm water. Remove contaminated clothing and launder before re-use. For inhalation, remove exposed individual to fresh air. Give oxygen with artificial respiration as needed. Seek medical attention for treatment, observation and support as needed. For ingestion, rinse out mouth immediately. Give exposed individual 6-8 ounces of liquid. Do not induce vomiting unless advised by a physician.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: For spills, use absorbent materials such as vermiculite or other floor absorbent.

WASTE DISPOSAL METHOD: Do not flush water to sewer, watershed or waterway. Use absorbent or kitty litter to dry product before disposal. Dispose of product with applicable local, county, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep material from freezing. Do not store above 120 F or below 34 F. Close container after each use. Keep out of reach of children. Use adequate ventilation when handling or applying this product.

OTHER PRECAUTIONS: None.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Use (NIOSH/MSA approved) mechanical filter respirator to remove solid airborne particles from overspray.

VENTILATION: Product is designed for indoor use. Use ventilation as required.

PROTECTIVE GLOVES: Wear protective gloves that are impermeable such as neoprene or resistant gloves such as butyl rubber.

EYE PROTECTION: Chemical splash goggles would be ideal but safety glasses in compliance with OSHA are also recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: To reduce or prevent skin contact, wear impervious clothing or boots.

WORK/HYGIENIC PRACTICES: Wash hands thoroughly before eating or using restroom.

SECTION IX - DISCLAIMER

DISCLAIMER: The above information refers to the product as currently manufactured. A common practice is end-user addition of additives to provide different characteristics. When this is done, the composition of the product and attendant hazards may be altered. Litex is not liable.